



## Teflon Hook-up Wires 鐵弗龍線

Trade No. 商業編號	Conductor AWG 導體	Conductor Construction 導體結構	Conductor O.D. 導體 O.D.	Nominal O.D. 完成線徑	Max Conductor Resistance 20°C Ω /KM	Max Conductor Resistance 20 M Ω -KM	Dielectric Strength V/Min	UL-Style	Temp. Rating Voltage. Rating
M001	30	7/0.1	0.3	1.44	354	2500	2000	1330	FEP 200°C,600V
M002	28	7/0.127	0.38	1.52	224	2500	2000	1330	FEP 200°C,600V
M003	26	7/0.16	0.48	1.62	140	2500	2000	1330	FEP 200°C,600V
M004	24	7/0.2	0.60	1.74	93.3	2500	2000	1330	FEP 200°C,600V
M005	22	7/0.254	0.76	1.90	55	2500	2000	1330	FEP 200°C,600V
M006	20	7/0.32	0.96	2.10	34.6	2500	2000	1330	FEP 200°C,600V
M007	18	7/0.4	1.20	2.36	21.8	2500	2000	1330	FEP 200°C,600V
M008	30	1/0.254	0.254	1.39	361	2500	2000	1330	FEP 200°C,600V
M009	28	1/0.32	0.320	1.46	227	2500	2000	1330	FEP 200°C,600V
M010	26	1/0.404	0.404	1.54	143	2500	2000	1330	FEP 200°C,600V
M011	24	1/0.511	0.511	1.65	89.4	2500	2000	1330	FEP 200°C,600V
M012	22	1/0.643	0.643	1.78	54.3	2500	2000	1330	FEP 200°C,600V
M013	20	1/0.813	0.813	1.95	33.9	2500	2000	1330	FEP 200°C,600V
M014	18	1/1.024	1.024	2.16	21.4	2500	2000	1330	FEP 200°C,600V
M015	30	7/0.1	0.3	1.44	354	2500	2000	1331	FEP 150°C,600V
M016	28	7/0.127	0.38	1.52	224	2500	2000	1331	FEP 150°C,600V
M017	26	7/0.16	0.48	1.62	140	2500	2000	1331	FEP 150°C,600V
M018	24	7/0.2	0.6	1.74	85.9	2500	2000	1331	FEP 150°C,600V
M019	22	7/0.254	0.76	1.9	55	2500	2000	1331	FEP 150°C,600V
M020	30	1/0.254	0.254	1.39	361	2500	2000	1331	FEP 150°C,600V
M021	28	1/0.32	0.32	1.46	227	2500	2000	1331	FEP 150°C,600V
M022	30	7/0.1	0.3	1.04	354	1000	2000	1332	FEP 200°C,300V
M023	28	7/0.127	0.38	1.12	224	1000	2000	1332	FEP 200°C,300V
M024	26	7/0.16	0.48	1.22	140	1000	2000	1332	FEP 200°C,300V
M025	24	7/0.2	0.6	1.34	85.9	1000	2000	1332	FEP 200°C,300V
M026	22	7/0.254	0.76	1.50	55	1000	2000	1332	FEP 200°C,300V
M027	30	1/0.254	0.254	0.99	361	1000	2000	1332	FEP 200°C,300V
M028	28	1/0.32	0.320	1.06	227	1000	2000	1332	FEP 200°C,300V
M029	26	1/0.404	0.404	1.14	143	1000	2000	1332	FEP 200°C,300V
M030	24	1/0.511	0.511	1.25	89.4	1000	2000	1332	FEP 200°C,300V
M031	22	1/0.643	0.643	1.38	54.3	1000	2000	1332	FEP 200°C,300V
M032	30	7/0.1	0.3	1.04	354	1000	2000	1333	FEP 200°C,300V
M033	28	7/0.127	0.38	1.12	224	1000	2000	1333	FEP 200°C,300V
M034	26	7/0.16	0.48	1.22	140	1000	2000	1333	FEP 200°C,300V

## Teflon Hook-up Wires 鐵弗龍線

Trade No. 商業編號	Conductor AWG 導體	Conductor Construction 導體結構	Conductor O.D. 導體 O.D.	Nominal O.D. 完成線徑	Max Conductor Resistance 20°C Ω /KM	Max Conductor Resistance 20°C M Ω -KM	Dielectric Strength V/Min	UL-Style	Temp. Rating Voltage. Rating
M035	24	7/0.2	0.6	1.34	85.9	1000	2000	1333	FEP 200°C,300V
M036	22	7/0.254	0.76	1.50	55	1000	2000	1333	FEP 200°C,300V
M037	30	1/0.254	0.254	0.99	361	1000	2000	1333	FEP 200°C,300V
M038	28	1/0.32	0.32	1.06	227	1000	2000	1333	FEP 200°C,300V
M039	32	7/0.08	0.24	0.98	589	1000	2000	1929	PFA 200°C,300V
M040	30	7/0.1	0.30	1.04	354	1000	2000	1929	PFA 200°C,300V
M041	28	7/0.127	0.38	1.12	224	1000	2000	1929	PFA 200°C,300V
M042	26	7/0.16	0.48	1.22	140	1000	2000	1929	PFA 200°C,300V
M043	24	7/0.2	0.60	1.34	85.9	1000	2000	1929	PFA 200°C,300V
M044	22	7/0.254	0.76	1.50	55	1000	2000	1929	PFA 200°C,300V
M045	30	1/0.254	0.254	0.99	361	1000	2000	1929	PFA 200°C,300V
M046	28	1/0.32	0.32	0.99	227	1000	2000	1929	PFA 200°C,300V
M047	26	1/0.404	0.404	1.14	143	1000	2000	1929	PFA 200 ,300V
M048	24	1/0.511	0.511	1.25	89.4	1000	2000	1929	PFA 200°C,300V
M049	22	1/0.643	0.643	1.38	54.3	1000	2000	1929	PFA 200°C,300V
M050	30	7/0.1	0.3	1.44	354	2500	2000	1930	PFA 200°C,600V
M051	28	7/0.127	0.38	1.52	224	2500	2000	1930	PFA 200°C,600V
M052	26	7/0.16	0.48	1.62	140	2500	2000	1930	PFA 200°C,600V
M053	24	7/0.2	0.60	1.74	85.9	2500	2000	1930	PFA 200°C,600V
M054	22	7/0.254	0.76	1.90	55	2500	2000	1930	PFA 200°C,600V
M055	30	1/0.254	0.254	1.39	361	2500	2000	1930	PFA 200°C,600V
M056	28	1/0.32	0.32	1.46	227	2500	2000	1930	PFA 200°C,600V
M057	26	1/0.404	0.57	1.54	143	2500	2000	1930	PFA 200°C,600V
M058	24	1/0.511	0.511	1.65	89.4	2500	2000	1930	PFA 200°C,600V
M059	22	1/0.643	0.643	1.78	54.3	2500	2000	1930	PFA 200°C,600V
M060	20	1/0.813	0.813	1.95	33.9	2500	2000	1930	PFA 200°C,600V
M061	18	1/0.024	1.024	2.16	21.4	2500	2000	1930	PFA 200°C,600V
M062	22	1/0.643	0.643	1.10	54.3	500	500	1516	ETFE 105°C
M063	22	7/0.254	0.76	1.10	55.0	500	500	1516	ETFE 105°C
M064	20	1/0.813	0.813	1.11	33.9	500	500	1516	ETFE 105°C
M065	30	1/0.254	0.254	0.61	361	500	500	1517	ETFE 105°C
M066	28	1/0.32	0.32	0.68	227	500	500	1517	ETFE 105°C
M067	26	1/0.404	0.404	0.76	143	500	500	1517	ETFE 105°C